

Record 15: JP7126316A**(ENG) PRODUCTION OF ETHYLENE COPOLYMER****Assignee:** SHOWA DENKO KK

[no drawing available]

Inventor(s): MONOI HISASHI ; YAMAMOTO MASAKAZU
; MATSUOKA TORU**Application No:** JP 27703993 A**Filing Date:** 19931105**Issue/Publication Date:** 19950516

Abstract: (ENG) <sec>PURPOSE: To obtain an ethylene copolymer for hollow molding which has an excellent balance between rigidity and environmental-stress cracking resistance(ESCR) through two-stage copolymerization using a Ziegler catalyst by adding a specific compound to the second-stage polymerization zone. CONSTITUTION: An ethylene copolymer is produced by the two-stage copolymerization of ethylene and an α -olefin using a Ziegler catalyst. High-mol. components are produced in the first polymerization zone, and low-mol. components are then produced in the second polymerization zone in the presence of a compound (a) represented by the formula (wherein R₁ to R₄ each independently is hydrogen, an alkyl, an aryl, an aralkyl, an alkoxy, etc., and (n) is an integer of 1-10). The compound (a) is fed in such an amount that the molar ratio of the compound (a) to the Ti atoms contained in the catalyst present in the second-stage polymerizer is about 0.1-50.</sec>

Priority Data: JP 27703993 19931105 A X;**IPC (International Class):** C08F004647; C08F01002